

Atenschutz-Systeme Breathing Protection Systems



System I

- 1St Atemschutzvollmaske „X-Plore 6300“
- 1St Kombinationsfilter

Sicherheit aus einem Guss. Die Vollmasken schützen Gesicht und Augen gegen aggressive Medien. Der Rundgewindeanschluss nach EN 148-1 passt für Atemfilter, Gebläsefiltergeräte, Pressluftatmer und Schlauchgeräte. X-Plore 6300 Masken entsprechen der EN 136 Cl. 3 oder Cl. 2 und sind CE gekennzeichnet. Nur mit Normaldruck-Lungenautomaten, Gebläsefiltergeräten, Normaldruck-Schlauchgeräten oder Atemfiltern mit Gewindeanschluss entsprechend EN148-1(RA) verwenden. Für Brillenträger lässt sich eine Maskenbrille einsetzen.

System I

- 1pc Full Face Mask „X-Plore 6300
- 1pc Combination filter

The full face masks protect the face and eyes against aggressive media. The standard thread connection conforming to EN 148-1 is designed to fit respiratory filters, power assisted devices, self-contained breathing apparatus and compressed air line breathing apparatus. Only use certified respiratory apparatus. X-Plore 6300 Masks are designed according EN 136 Cl. 3 or Cl. 2 and carry CE mark. Only use with approved normal pressure compressed air breathing apparatus, power assisted filtering devices, normal pressure compressed air line breathing apparatus or respiratory filters with threaded connections conforming to EN 148-1(RA). Special goggles are available to retrofitting.



System II

- 1St System I mit 3ST Kombinationsfilter
- 1St Gebläseeinheit “X-Plore 7500“
- 1St Komfort Gürtel
- 1St Faltenschlauch “X-Plore RD 40“
- 1St NIMH Akku und Akku Ladegerät

System II entspricht System I ergänzt durch die Gebläseeinheit die das leichtere Atmen ermöglicht.

System II

- 1pc System I with 3pc combination filter
- 1pc power assisted filtering device
- 1pc comfort belt
- 1pc pleated hose “X-Plore RD 40“
- 1pc NIMH battery and battery charger

System II corresponds to System I added with the power assisted filtering device to facilitate breathing.



System III

- ① 1St Atemschutzvollmaske “X-Plore 6300“
- ② 1St Lungenautomat
- ③ 1St Atemluftschlauch (Länge-optional)
- ④ 1St Feinfilter
- ⑤ 1St Gürtelgarnitur Set

System III ermöglicht durch den Lungenautomat die Frischluftzufuhr. Der Lungenautomat ist zur Verwendung in Verbindung mit zugelassenen Pressluftatmer- Grundgeräten, Atemanschluss und Flaschen schützt der Lungenautomat PSS N den Träger bei der Arbeit in kombinierter, gashaltiger Umgebung und bei Sauerstoffmangel. TYP N-40mm Gewinde nach EN 148-1. Bei Anschluss an den Atemanschluss ermöglicht die spezielle Drehfunktion des Lungenautomaten Anschlussstückes und des Handrads dem Lungenautomaten, bei Kopf- und Körperbewegungen des Benutzers den Atemanschluss zu schwenken.

System III

- ① 1pc full face Mask “X-Plore 6300“
- ② 1pc Lung Demand Valve
- ③ 1pc breathing hose (length-optional)
- ④ 1pc fine filter
- ⑤ 1pc belt set

System III enables fresh air breathing with the Lung Demand valve. The Lung demand valve, used with approved compressed air respiratory protection equipment, face piece and cylinder combinations, provide the wearer with respiratory protection when working in a contaminated, or oxygen deficient gaseous atmosphere. Type N- 40mm Thread to EN 148-1. When the demand valve is fitted to the face piece the swivel feature of the handwheel allows a degree of radial movement of the demand valve